



ISO/IEC 17025;2017

מעבדות כיול

תעודת הסמכה מס' 400 שקילה ייצור בע"מ

כתובת אתר ייחוס: אלון תבור 17, קיסריה, 3088900

עד יום: 20.07.2025

בתוקף מיום:21.06.2023

הארגון נבדק ונבחן על ידי הרשות הלאומית להסמכת מעבדות (להלן הרשות) ונמצא ראוי להסמכה בהתאם לנספח פירוט היקף ההסמכה המצורף לתעודה זו, המהווה חלק בלתי נפרד ממנה ומספרו זהה למספר התעודה.

הסמכה מצביעה על כשירות מקצועית ותפעול מערכת ניהול איכות בעלת הכרה בינלאומית.

הארגון המוסמך על ידי הרשות, עומד בתקנים/ בדרישות המפורטים מעלה. דרישות התקנים הם לכשירות מקצועית ולמערכות ניהול, שהינן הכרחיות למתן תוצאות אמינות. הסמכה זו ניתנה בהתאם לכללי ISO/IEC 17011:2017 לפיהם פועלת הרשות ובמסגרתם מקיימת פיקוח שוטף על הארגון לצורך בחינת תפקודו המתמשך בהתאם לדרישות ההסמכה. ההסמכה תקפה כל עוד הארגון עונה לאמות המידה שנקבעו על ידי הרשות.

.(EA) European Accreditation Cooperation מול ארגון (MLA) מול הסכם הכרה רב צדדי

תעודה זו אינה מהווה אישור לפי סעיף 12 לחוק התקנים.

21/07/2019 :תאריך הסמכה ראשון

אתי פלר מנכ"ל

הרשות הלאומית להסמכת מעבדות

Date of signature 21/06/2023

Page No.

of: 5





Calibration Laboratory

ISO/IEC 17025;2017

Until: 20.07.2025

Accreditation Certificate No. 400 Shkila manufactures L.T.D

Main site address: Alon Tavor 17 St., Caesarea, 3088900, Israel

Valid from:21.06.2023

The organization was assessed by the Israel Laboratory Accreditation Authority (ISRAC) and found to be worthy of accreditation to the detailed schedule attached.

The schedule is an integral part of this certificate and is numbered with the above certificate number.

Accreditation demonstrates technical competence and operation of an internationally recognized quality management system.

The organization accredited by ISRAC complies with the standards/requirements mentioned above, meets the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically competent results. This accreditation is granted in accordance with the requirements of ISO/IEC 17011:2017, and entails periodic surveillance and reassessment by ISRAC to ensure that the organization continues to comply with the accreditation requirements.

The accreditation is valid provided that the organization continues to meet the criteria as laid down by ISRAC. ISRAC is an EA-MLA (European Accreditation Cooperation Multi-Lateral Agreement) signatory.

This certificate does not constitute an approval in accordance with article 12 of the standard law.

Date of first accreditation: 21/07/2019

Etty Feller
General Manager
Israel Laboratory Accreditation Authority

Date of signature 21/06/2023 Page No. 2 of: 5

Department: Calibration Laboratory ISO/IEC 17025; 2017

Accreditation No. 400

Name and Address:

Organization name SHKILA manufactures L.T.D.

Address Alon Tavor 17 St., Caesarea, 3088900, Israel

 Phone
 +972-4-6274411

 Fax
 +972-4-6274433

 E-mail (contact person)
 faby@shkila.com

Site: P or T or M, P-Permanent, T-Temporary, M-Mobile

A permanent (P) or temporary (T) place, or a stationary or mobile (M) facility, at or from which the organization performs activities forming part of its scope of accreditation, starting from sampling to final issuance of a report or certificate and / or quality system activities. A temporary (T) site is a site established under the responsibility of an accredited permanent site. All activities performed at a temporary site are the responsibility of the permanent site. An outdoors work is also considered to be a temporary site. Temporary site will be a site that involves work for special project and the activity will be defined in time (up to 2 years).

Type of Scopes: A- Fixed, C- Flexible scope in analytical tests: Type of matrix, analytes, experimental systems and/or analytical characteristics may be subject to changes, in accordance with the laboratory's approved and documented procedures. For details, please refer to the list of Accredited Tests, available from the laboratory upon request.

Date of signature 21/06/2023 Page No. 3 of: 3

Department:

Calibration Laboratory ISO/IEC 17025:2017

Accreditation No. 400

| Item | Scope Type | Site | Measurand Instrument, Gauge | | Range [Including margins] (Does not include margins) | Uncertainty of Measurement ¹ | Reference Documents | Remarks |
|---------|---------------|--------|-----------------------------|---------|--|---|---------------------|---|
| Calibre | ation – | Physic | al Quantities - Mass | | כיול - גדלים פיזיקליים - מסה | | | |
| 1 | A | P | Mass | מסה | 1 mg | 0.007 mg | OIML R 111 | Available standard weights: E2 from 1 mg to 20 kg, |
| 2 | A | P | Weights | משקולות | 2 mg | 0.007 mg | | M1 10 kg (65 pcs) M2 100 kg (1pcs) |
| 3 | A | P | | | 5 mg | 0.007 mg | | M2 200 kg (2pcs) M2 500 kg (1pcs) |
| 4 | A | P | | | 10 mg | 0.007 mg | | 1 mg - 20 kg |
| 5 | A | P | | | 20 mg | 0.007 mg | | נבדקת החל מרמת דיוק F1 |
| 6 | A | P | | | 50 mg | 0.007 mg | | 50 kg – 1000 kg |
| 7 | A | P | | | 100 mg | 0.010 mg | | M2 נבדקת החל מרמת דיוק |
| 8 | A | P | | | 200 mg | 0.010 mg | | |
| 9 | A | P | | | 500 mg | 0.019 mg | | |
| 10 | A | P | | | 1 g | 0.017 mg | | |
| 11 | A | P | | | 2 g | 0.024 mg | | |
| 12 | A | P | | | 5 g | 0.012 mg | | |
| 13 | A | P | | | 10 g | 0.030 mg | | |
| 14 | A | P | | | 20 g | 0.048 mg | | |
| 15 | A | P | | | 50 g | 0.047 mg | | |
| 16 | A | P | | | 100 g | 0.109 mg | | |
| 17 | A | P | | | 200 g | 0.086 mg | | |
| 18 | A | P | | | 500 g | 0.83 mg | | |
| 19 | A | P | | | 1 kg | 1.5 mg | | |

Date of signature 21/06/2023

Page No. 4 of: 5



Department:

Calibration Laboratory

ISO/IEC 17025:2017

Accreditation No. 400

| Item | Scope Type | Site | Measurand Instrument, Gauge | | Range [Including margins] (Does not include margins) | Uncertainty of Measurement ¹ | Reference Documents | Remarks |
|---------|---------------|--------|-----------------------------|----------------------|--|---|------------------------------|--|
| Calibra | ation – | Physic | al Quantities - Mass | | כיול - גדלים פיזיקליים - מסה | | | |
| 20 | A | P | | | 2 kg | 2.7 mg | | |
| 21 | A | P | | | 5 kg | 4.7 mg | | |
| 22 | A | P | | | 10 kg | 5.3 mg | | |
| 23 | A | P | | | $20 \mathrm{~kg}$ | 65 mg | | |
| 24 | | | | | 50 kg | 1.4 g | | |
| 25 | | | | | 100 kg | 1.5 g | | |
| 26 | | | | | 200 kg | 7.4 g | | |
| 27 | | | | | 500 kg | 8.4 g | | |
| 28 | | | | | 1000 kg | 48 g | | |
| 29 | A | P;T | p;T Non automatic weighting | מאזניים לא אוטומטיים | Up to 1000 kg] | $2\times \sqrt{\left(\frac{res}{res}\right)^2 + \left(\frac{mpe}{res}\right)^2}$ | OIML R 76-1 EURAMET cg-18 | res - resolution of the balance |
| | | | machines | | | $2 \times \sqrt{\left(\frac{res}{3.46}\right)^2 + \left(\frac{mpe}{1.74}\right)^2}$ | | mpe - maximum permissible error of the weights according to OIML R 111 |
| 30 | A | P;T | | | (1000 kg to 3000 kg] | 0.3 kg | | Available standard weights: |
| | | | | | | | | E2 from 1 mg to 10 kg, |
| | | | | | | | | M1 from 10 kg (65 pcs) to 20 kg (25 pcs) |

¹⁾ The uncertainty covered by the CMC expressed as the standard measurement uncertainty multiplied by the coverage factor k such that the coverage probability corresponds to approximately 95 %.